



POS - BARCODE - AUTO ID  
Your POS Marketplace



## POS OF AMERICA Thermal Receipt Printer

Designed to set a New Standard for Value, the POS OF AMERICA Thermal Receipt Printer sets the bar in performance versus price. The POS OF AMERICA Thermal Receipt Printer has been engineered to withstand the harshest of environments that require steadfast performance. Perfect for high-volume retail and hospitality operations, the POS OF AMERICA Receipt Printer features fast image printing, JamFree Autocutter Technology, and includes the interface cable standard with all models.



### Key Features

- Interface cable included
- Swappable interface cards
- ESC/POS and OPOS compatible
- JamFree Autocutter Technology
- 160mm per Second Text/Image Print Speed
- USB or USB/Serial, USB/ Parallel, USB/ Ethernet
- 3-Year Advanced Replacement Protection

**POS OF AMERICA** 6303 Blue Lagoon Dr Suite 400 Miami FL 33126  
www.posofamerica.com info@posofamerica.com Tel 786 331 9160 Fax 786 752 3302

# POS OF AMERICA Thermal Receipt Printer

## Specifications

Interface Details USB 2.0 USB 2.  
Emulation ESC/POS Command Compatible  
Print Method Direct Thermal  
Printing Speed 6.3"/sec 160mm/sec  
Dot Density 180 DPI x 180 DPI  
Dot Pitch 0.005551" x 0.005551"  
Printing Direction Unidirectional with Friction Feed  
Sensors Paper End, Cover Open, Paper Low  
**CASH DRAWER PORTS** 2 Circuits (24V, 1A max)  
**RELIABILITY** TPH Life 99.42 miles MCBF 60,000,000 Lines

### PAPER

Type Thermal Paper  
Width 1.9" (50mm) - 3.125" (82.5mm)  
Thickness 0.002" (0.06mm) - 0.0035" (0.09mm)  
Roll Diameter Max 3.27" (83mm)  
Roll Core Inner Diameter 0.492" (12.5mm) ± 0.019 "(0.5mm)  
**CHARACTER SET** Alpha Numeric Character 95 Extended Graphics 128 x 18 page (1 space per page)  
International Characters 14  
**CHARACTER/LINE** Font A (12 x24) 42 columns Font B (9 x17) 56 columns  
**BARCODES SUPPORTED** EAN-8, EAN-13, CODE 39, ITF, UPC-A, CODABAR, CODE 93, CODE 128, PDF 417(2D)

### AUTO CUTTER

Type JamFree auto-retracting Guillotine  
Life 1,500,000 Cuts  
Cutting Method Full/Partial Cut

### PHYSICAL

Dimension 6."(w) x 7.60"(D) x 5.80"(H)  
Weight 3.4 lbs  
Color Black

**ELECTRICAL** (input)100 - 240 Vac 50/50 Hz (output) 24Vdc/2.5A

### ENVIROMENTAL

Temperature 41°F to 104°F operating -4°F to 140°F storage  
Humidity 35%-80% non condensing (operation) 10%-90% non condensing (storage)

**WARRANTY** 3 Year 2 year on autocutter assembly and print head

**CERTIFICATIONS** FCC, MIC, UL, CE, CCC, RoHs

**OPERATING SYSTEM** WIN 95/WIN 98/WIN 2000/WIN XP/VISTA/Win 7/OPOS driver available

### ACCESSORIES

RPCARD-2P Parallel Interface Card  
RPCARD-2S Serial Interface Card  
RPCARD-2E Ethernet Interface Card